TRANSFER OIL
Pure Fluid Attitude

Crimping details

Last updated: 14/09/2026

15R - CNG 5000 HOSE

Transfer Oil reserve the rights to introduce improving modifications whenever necessary.
The listed crimping data have been developed in Transfer Oil R&D laboratories and refer to tests carried out on thermoplastic hoses manufactured by Transfer Oil, and specific Transfer Oil approved ferrules and fittings.
Such values are anyway to be considered advisory and not binding for Transfer Oil because the impossibility to consider technical variability like the swaging machine used, the set of crimping dies used, the speed of the crimping process, the tolerances of each single item involved, etc.
For new applications or for hoses, ferrules and fittings not listed in this file please contact us, and we will be happy to help you in finding the best match.

WARNING: when using VHP inserts always check bore collapse using go/no go bore gauge part n° SXC---. If needed adjust crimping diameter in order to obtain the optimal bore collapse

Part no.	Description	Dash	Inches	DN	ID (mm)	OD (mm)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Ferrule part n°	Ferrule material	Crimping diameter (mm)	Crimping diameter (inch)	Bore collapse (mm)	Bore collapse (inch)	go/nogo gauge	dies set* (mm)
15R2	1/4 CNG 5000 RED	-4	1/4	DN6	6.5	13.7	350	5000	1400	20000	SAF821	Stainless Steel (A316L)	16.9	0.665	0.7	0.0276	SXC821	16
15R2	1/4 CNG 5000 RED	-4	1/4	DN6	6.5	13.7	350	5000	1400	20000	SAF121	Carbon Steel	16.9	0.665	0.7	0.0276	SXC821	16
15R4	3/8 CNG 5000 RED	-6	3/8	DN10	9.7	18.9	350	5000	1400	20000	SAF841	Stainless Steel (A316L)	22.8	0.898	0.7	0.0276	SXC841	19
15R4	3/8 CNG 5000 RED	-6	3/8	DN10	9.7	18.9	350	5000	1400	20000	SAF141	Carbon Steel	22.8	0.898	0.7	0.0276	SXC841	19
15R5	1/2 CNG 5000 RED	-8	1/2	DN12	13.0	22.5	350	5000	1400	20000	SAF851	Stainless Steel (A316L)	27.8	1.094	0.7	0.0276	SXC852	27
15R5	1/2 CNG 5000 RED	-8	1/2	DN12	13.0	22.5	350	5000	1400	20000	SAF151	Carbon Steel	27.8	1.094	0.7	0.0276	SXC852	27
15R7	3/4 CNG 5000 RED	-12	3/4	DN20	19.5	29.6	350	5000	1400	20000	SAF872	Stainless Steel (A316L)	35	1.378	1	0.0394	SXC873	31
15R7	3/4 CNG 5000 RED	-12	3/4	DN20	19.5	29.6	350	5000	1400	20000	SAF172	Carbon Steel	35	1.378	1	0.0394	SXC873	31
15R8	1 CNG 5000 RED	-16	1	DN25	25.9	39.0	350	5000	1400	20000	SAF881	Stainless Steel (A316L)	44.7	1.760	1.3	0.0512	SXC882	41
15R8	1 CNG 5000 RED	-16	1	DN25	25.9	39.0	350	5000	1400	20000	SAF181	Carbon Steel	44.7	1.760	1.3	0.0512	SXC882	41

* The dies set indicated are a standard die set for FinnPower FP20 swaging machine, as used in the R&D laboratory of Transfer Oil, used to verify the swaging parameters.