TRANSFER OIL
Pure Fluid Attitude

110 - ECOLOGY 200 HD下水道清洗管

高压下水道清洗用热塑软管，额定工作压力达 200 bar (2900 psi)



产品特点

内管

热塑性聚合物

增强层

一层或两层聚酯纤维编织外加一层与融入外塑层的聚酯纤维层

外胶层

聚氨酯 - 蓝色 - 无针刺 - 激光打标

应用场合

常见下水道清洗车及相关应用；用于高湿度环境下的清洗设备

产品特点

融入一层纤维编织层的蓝色外塑层，提升了软管的耐磨性和使用寿命；单根软管长；优异的抗压和抗剪切性能；与同类橡胶软管相比重量轻非常耐磨的重载荷下水道清洗用软管，耐温范围达-40 °C to 60 °C (-40 °F to 140 °F)。该软管专为潮湿环境下应用不降低性能以确保其长周期使用而设计；可提供带BSP 和/或NPT 接头软管总成；如需要，也可以供其它接头型式。不适用于液压应用。仅供应总成：请联系我们销售代表了解详细信息。

温度范围

-40 °C to 60 °C (-40 °F to 140 °F)

产品标识

TRANSFER OIL - TO INDUSTRIAL - Part No - ECOLOGY 200 HD - SEWER CLEANING HOSE - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

零件号	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	安全系数	弯曲半径 (mm)	弯曲半径 (inch)	重量 (gr/m)	重量 (lb/ft)	碳钢套筒	A316L不锈钢套筒
1105	DN12	1/2	-8	13.0	21.4	200	500	0.512	0.843	2900	7200	2.5:1	75	2.95	228	0.153	SA5151	SA5851
1106	DN16	5/8	-10	16.3	24.4	200	500	0.642	0.961	2900	7250	2.5:1	100	3.94	264	0.177	SA5161	SA5861
1107	DN20	3/4	-12	19.6	29.7	200	500	0.772	1.169	2900	7250	2.5:1	120	4.72	412	0.277	SA5171	SA5871
1108	DN25	1	-16	25.6	37.5	200	500	1.008	1.476	2900	7200	2.5:1	155	6.10	605	0.407	SA5181	SA5881
1109	DN32	1+1/4	-20	32.4	47.2	200	500	1.276	1.858	2900	7200	2.5:1	240	9.45	1001	0.673	SA5191	SA5891
110T	DN38	1+1/2	-24	38.4	55.6	200	500	1.512	2.189	2900	7200	2.5:1	300	11.81	1340	0.900	SA51T1	SA58T1

卷筒包装的软管总成

EIEXXX	1/2" ECOLOGY 200 HD	1/2" M/F BSPP
EIFXXX	1/2" ECOLOGY 200 HD	1/2" M/M NPT
EIQXXX	1/2" ECOLOGY 200 HD	1/2" M/F BSPP - AISI A316L
EIRXXX	1/2" ECOLOGY 200 HD	1/2" M/M NPT - AISI A316L
E0GXXX	5/8" ECOLOGY 200 HD	3/4" M/F BSPP
E0HXXX	5/8" ECOLOGY 200 HD	3/4" M/M NPT
E0SXXX	5/8" ECOLOGY 200 HD	3/4" M/F BSPP - AISI A316L
E0TXXX	5/8" ECOLOGY 200 HD	3/4" M/M NPT - AISI A316L
EJGXXX	3/4" ECOLOGY 200 HD	3/4" M/F BSP
EJHXXX	3/4" ECOLOGY 200 HD	3/4" M/M NPT
EJSXXX	3/4" ECOLOGY 200 HD	3/4" M/F BSP - AISI A316L
EJTXXX	3/4" ECOLOGY 200 HD	3/4" M/M NPT - AISI A316L
EKIXXX	1" ECOLOGY 200 HD	1" M/F BSP
EKJXXX	1" ECOLOGY 200 HD	1" M/M NPT
EKUXXX	1" ECOLOGY 200 HD	1" M/F BSP - AISI A316L
EKVXXX	1" ECOLOGY 200 HD	1" M/M NPT - AISI A316L
ELKXXX	1 1/4" ECOLOGY 200 HD	1 1/4" M/F BSP
ELLXXX	1 1/4" ECOLOGY 200 HD	1 1/4" M/M NPT
ELWXXX	1 1/4" ECOLOGY 200 HD	1 1/4" M/F BSP - AISI A316L
ELXXXX	1 1/4" ECOLOGY 200 HD	1 1/4" M/M NPT - AISI A316L

XXX = 软管总成长度（米） (1mt = 3,28 ft)

不带卷筒包装软管总成

FIEXXX	1/2" ECOLOGY 200 HD	1/2" M/F BSPP
FIFXXX	1/2" ECOLOGY 200 HD	1/2" M/M NPT
FIQXXX	1/2" ECOLOGY 200 HD	1/2" M/F BSPP - AISI A316L
FIRXXX	1/2" ECOLOGY 200 HD	1/2" M/M NPT - AISI A316L
F0GXXX	5/8" ECOLOGY 200 HD	3/4" M/F BSPP
F0HXXX	5/8" ECOLOGY 200 HD	3/4" M/M NPT
F0SXXX	5/8" ECOLOGY 200 HD	3/4" M/F BSPP - AISI A316L
F0TXXX	5/8" ECOLOGY 200 HD	3/4" M/M NPT - AISI A316L
FJGXXX	3/4" ECOLOGY 200 HD	3/4" M/F BSP
FJHXXX	3/4" ECOLOGY 200 HD	3/4" M/M NPT
FJSXXX	3/4" ECOLOGY 200 HD	3/4" M/F BSP - AISI A316L
FJTXXX	3/4" ECOLOGY 200 HD	3/4" M/M NPT - AISI A316L
FKIXXX	1" ECOLOGY 200 HD	1" M/F BSP
FKJXXX	1" ECOLOGY 200 HD	1" M/M NPT
FKUXXX	1" ECOLOGY 200 HD	1" M/F BSP - AISI A316L
FKVXXX	1" ECOLOGY 200 HD	1" M/M NPT - AISI A316L
ELKXXX	1 1/4" ECOLOGY 200 HD	1 1/4" M/F BSP
ELLXXX	1 1/4" ECOLOGY 200 HD	1 1/4" M/M NPT
ELWXXX	1 1/4" ECOLOGY 200 HD	1 1/4" M/F BSP - AISI A316L
ELXXXX	1 1/4" ECOLOGY 200 HD	1 1/4" M/M NPT - AISI A316L

XXX = 软管总成长度（米） (1mt = 3,28 ft)

为提高产品性能和可靠性，所示尺寸和数值可在不事先通知的情况下更改。
Transfer Oil S.p.A.对本规格表中出现的错误不承担任何责任。
文本日期: 26/11/2026
www.transferoil.com