



TRANSFER OIL

Pure Fluid Attitude



107 - PUSH-ON NON CONDUCTIVE

Non conductive thermoplastic constant pressure hose for low pressure air and water line up to 20 bar (290 psi)



FEATURES

Inner Tube

Polyurethane

Reinforcement

One braid of synthetic fiber

Cover

Polyurethane - orange - laser branding

Applications

Low pressure air and water line - Free of paint affecting substances
- LABS free

Features

Polyurethane tube and cover for high flexing giving long service life - Abrasion resistant cover for optimum wear resistance - Push on fitting assembly without crimping.

Description

Low pressure air and water line suitable for high flexing applications.

Temperature Range

-40 °C to +80 °C (-40 °F to +176 °F)

Standard Branding

TRANSFER OIL - TO INDUSTRIAL - Part No - PUSH-ON NON CONDUCTIVE - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
1072	DN6	1/4	-4	6.3	11.2	20	80	0.248	0.441	290	1160	4:1	30	1.18	75	0.050		
1074	DN10	3/8	-6	9.5	15.0	20	80	0.374	0.591	290	1160	4:1	50	1.97	120	0.081		
1075	DN12	1/2	-8	12.7	19.1	20	80	0.500	0.752	290	1160	4:1	70	2.76	183	0.123		
1076	DN16	5/8	-10	16.2	23.1	20	80	0.638	0.909	290	1160	4:1	90	3.54	233	0.157		
1077	DN20	3/4	-12	19.0	26.0	20	80	0.748	1.024	290	1160	4:1	110	4.33	274	0.184		

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 13/04/2026

www.transferoil.com