



# TRANSFER OIL

Pure Fluid Attitude



## 169 - OFF SHORE MASTER 10k

Thermoplastic hose with MSHA approved cover, for off-shore high pressure hydraulic applications up to 700 bar (10000 psi)



### FEATURES

#### Inner Tube

Polyamide PA11 Rilsan® BESNO P40 TLO

#### Reinforcement

Up to three braids of aramid fiber

#### Cover

Polyurethane - black - non pinpricked - laser branding

#### Applications

Marine and off-shore equipment - ROVs (remotely operated vehicles) - BOP valves - Methanol injection - Seismic air gun systems

#### Features

Aramid reinforcement for high pressure performance- Lightweight - Flexible - Compact - Bonded construction - Abrasion resistant cover

#### Specifications

Hose manufactured to the applicable requirements of API 17E / ISO 13628-5

#### Temperature Range

-40 °C to 100 °C (-40 °F to 212 °F): limited to 70 °C ( 158 °F) and water based fluids

#### Description

High pressure hose suitable for petroleum synthetic or water based hydraulic fluids used in applications requiring increased resistance to seawater and saline environment. The size the pressure rating and special cover make this hose the optimal choice for off-shore equipment like ROVs (remotely operated vehicles) tethered underwater robots used in the off-shore industry. Specially designed hose can be manufactured upon request.

#### Vacuum Rating

-0,93 bar; -700 mm Hg|-13,5 psi; -27,5 inch Hg

### SPECIFICATIONS

Hose manufactured to the applicable requirements of API 17E / ISO 13628-5

#### Standard Branding

TRANSFER OIL - TO HYDRAULIC - Part No - OFF SHORE MASTER 10k - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
1692	DN6	1/4	-4	6.5	14.0	700	2800	0.256	0.551	10000	40000	4:1	35	1.38	134	0.090	SAF121	SAF821

---

## AVAILABLE INSERTS

---

Part	Dash	Inch	DN	F-BSPP	F-DKOL	F-DKOS	F-JIC	F-NPSM	M-BSPP	M-BSPT	M-CEL	M-CES	M-NPT
1692	-4	1/4	DN6	SOA	SOF	SOM	SOH	SOP	SOB	SOO	SOI	SOL	SOD

---

*Dimensions and values shown may be changed without prior notice to improve product performances and reliability.*

*Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.*

*Document date: 13/04/2026*

*[www.transferoil.com](http://www.transferoil.com)*