TRANSFER OIL
Pure Fluid Attitude

184 - AUTOMOTIVE LPG

Thermoplastic hose for LPG applications up to 30 bar (435 psi)



FEATURES

Inner Tube

Polyamide PA6

Reinforcement

One braid of synthetic fiber

Cover

Polyurethane - black - pinpricked - laser branding

Applications

Low pressure hose suitable for LPG applications

Features

Polyamide 6 tube construction compatible with LPG - Non metallic design with bonded construction - Lightweight and flexible - Abrasion resistant cover for long-lasting performance - Pinpricked cover

Description

Low pressure hose with black abrasion resistant cover suitable for LPG applications - Non metallic lightweight design for easy handling and manipulation.

Temperature Range

-40 °C to +100 °C (-40 °F to +212 °F)

Specifications

Hose meets applicable requirements of Regulation ECE/ONU n. 67/01. Certification number E7 67R01 00951.25

Standard Branding

TRANSFER OIL - Part No - AUTOMOTIVE LPG Class 1 - Inch Size - DN Size - WP bar / psi - 67R01 00951.25 - MADE IN ITALY - MM/YY - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
1841	DN5	3/16	-3	5.0	9.7	30	150	0.197	0.382	400	2000	5:1	25	0.98	60	0.040	SAB111	SAB811
1842	DN6	1/4	-4	6.5	12.0	30	150	0.256	0.472	400	2000	5:1	35	1.38	89	0.060	SAB121	SAB821

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.
Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.
Document date: 26/11/2026
www.transferoil.com