




# TRANSFER OIL

Pure Fluid Attitude



## Male NPT | Male BSPP



Part no.	Description	Side A	Side B	ID	HEX	L	MAWP
D9DMC 04ME0 401	1/4 M-NPT M-BSPP 1/4 15k 316D	1/4	1/4	4	5/8   16	37	15k
D9DMC 04ME0 601	1/4 M-NPT M-BSPP 3/8 15k 316D	1/4	3/8	5	3/4   19	40	15k
D9DMC 06ME0 401	3/8 M-NPT M-BSPP 1/4 15k 316D	3/8	1/4	4	3/4   19	40	15k
D9DMC 08ME0 401	1/2 M-NPT M-BSPP 1/4 15k 316D	1/2	1/4	4	1   26	46	15k
D9DMC 08ME0 601	1/2 M-NPT M-BSPP 3/8 15k 316D	1/2	3/8	5	1   26	47	15k
D9DMC 08ME0 801	1/2 M-NPT M-BSPP 1/2 15k 316D	1/2	1/2	7.5	1   26	50	15k
D9CMC 16ME06 01	1 M-NPT M-BSPP 3/8 10k 316D	1.00	3/8	5	1+1/2   38	56	10k
D9CMC 16ME08 01	1 M-NPT M-BSPP 1/2 10k 316D	1.00	1/2	7.5	1+1/2   38	59	10k

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 28/05/2026

[www.transferoil.com](http://www.transferoil.com)