TRANSFER OIL
Pure Fluid Attitude

Male Metric 24/60 | Male Metric 24/60



Part no.	Description	Side A	Side B	ID	HEX	L	MAWP
D9FMO12MO1201	M12 M-246|M-246 M12 30k 316D	M12	M12	3	1/2 | 13	28	30k
D9LMO14MO1401	M14 M-246|M-246 M14 50k 316D	M14	M14	5	5/8 | 16	31	50k
D9FMO16MO1601	M16 M-246|M-246 M16 30k 316D	M16	M16	6	3/4 | 19	33	30k
D9GMO18MO1801	M18 M-246|M-246 M18 40k 316D	M18	M18	7	7/8 | 22	38	40k
D9GMO20MO2001	M20 M-246|M-246 M20 40k 316D	M20	M20	8	7/8 | 22	38	40k
D9GMO22MO2201	M22 M-246|M-246 M22 40k 316D	M22	M22	10	1 | 26	42	40k
D9LMO24MO2401	M24 M-246|M-246 M24 50k 316D	M24	M24	12	1 | 26	42	45k
D9FMO30MO3001	M30 M-246|M-246 M30 30k 316D	M30	M30	16	1+3/8 | 35	48	30k
D9MMO36MO3601	M36 M-246|M-246 M36 24k 316D	M36	M36	20	1+1/2 | 38	54	24k
D9DMO42MO4201	M42 M-246|M-246 M42 15k 316D	M42	M42	20	1+3/4 | 45	58	15k

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.
Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.
Document date: 26/11/2026
www.transferoil.com