



TRANSFER OIL

Pure Fluid Attitude



035 - CP 3600 NEO

Thermoplastic high pressure hose with MSHA approved cover suitable for petroleum or synthetic based hydraulic fluids in hydraulic systems of forklifts. Up to 250 bar (3600 psi)



FEATURES

Inner Tube

Polyester elastomer

Reinforcement

One or two braids of synthetic fiber

Cover

Polyurethane - black - non pinpricked - laser branding

Applications

Forklift trucks

Features

2 polyester braid construction from 1/4"-DN6 onwards - Tight bend radii without cover wrinkling

Description

High pressure hose suitable for petroleum or synthetic based hydraulic fluids in hydraulic systems of forklifts. High level of flexibility.

Temperature Range

-40 °C to 100 °C (-40 °F to 212 °F): limited to 70 °C (158 °F) for air and water based fluids

Vacuum Rating

-0,93 bar; -700 mm Hg|-13,5 psi; -27,5 inch Hg

Specifications

SAE 100R18 // ISO3949-R18

Standard Branding

TRANSFER OIL - TO HYDRAULIC - Part No - CP 3600 NEO - Inch Size - DN Size - WP bar / psi - MSHA IC-305/02 - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
0351	DN5	3/16	-3	5.0	9.6	250	1000	0.197	0.378	3600	14400	4:1	25	0.98	60	0.040	SAB111	SAB811
0352	DN6	1/4	-4	6.5	13.0	250	1000	0.256	0.512	3600	14400	4:1	35	1.38	110	0.074	SAB121	SAB821
0353	DN8	5/16	-5	8.1	15.2	250	1000	0.319	0.598	3600	14400	4:1	45	1.77	140	0.094	SAB131	SAB831
0354	DN10	3/8	-6	9.7	18.0	250	1000	0.382	0.709	3600	14400	4:1	45	1.77	205	0.138	SAC141	SAC841

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 28/05/2026

www.transferoil.com