



# TRANSFER OIL

Pure Fluid Attitude



## 023 - R18 CPLFC 3000 NEO

Thermoplastic medium pressure hose with low friction cover suitable for petroleum or synthetic based hydraulic fluids of fork lifts. Up to 210 bar (3000 psi)



### FEATURES

#### Inner Tube

Polyester elastomer

#### Reinforcement

One or two braids of synthetic fiber

#### Cover

LFC polyurethane - black matte - non pinpricked - laser branding

#### Applications

Forklift trucks

#### Features

2 polyester braid construction from 5/16"-DN8 onwards - LFC cover anti-grip - Tight bend radii without cover wrinkling - highly resistant to abrasion

#### Description

Meets or exceeds SAE 100R18 specifications - Medium pressure hose suitable for petroleum or synthetic based hydraulic fluids in hydraulic systems of forklifts. High level of flexibility. Thanks to the anti-grip cover (LFC - Low Friction Cover) hoses can slide easily simplifying installation specially in hose bundles.

#### Temperature Range

-40 °C to 100 °C (-40 °F to 212 °F); limited to 70 °C (158 °F) for air and water based fluids

#### Vacuum Rating

-0,93 bar; -700 mm Hg|-13,5 psi; -27,5 inch Hg

#### Specifications

SAE 100R18 // ISO3949-R18

#### Standard Branding

**TRANSFER OIL** - TO HYDRAULIC - Part No - CPLFC 3000 NEO - SAE 100R18-Dash Size - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
0232	DN6	1/4	-4	6.5	11.8	210	840	0.256	0.465	3000	12000	4:1	35	1.38	90	0.060	SAB121	SAB821
0234	DN10	3/8	-6	9.7	16.5	210	840	0.382	0.650	3000	12000	4:1	45	1.77	155	0.104	SAB141	SAB841

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.  
Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 13/04/2026

www.transferoil.com