



# **085** - 2SB - TWO STEEL BRAIDS ANTIABRASION

Thermoplastic hose with MSHA approved cover and double steel reinforcement, for high pressure hydraulic applications from 150 to 400 bar (2100 to 5800 psi)



#### **FEATURES**

#### Inner Tube

Polyester elastomer

# Reinforcement

Two braids of steel wire

#### Cover

Polyurethane - black - non pinpricked - laser branding

## **Applications**

General hydraulic applications requiring high mechanical protection properties of hose and braid combined with high pressure - Construction equipment - Hoisting and handling equipments - Machine tools

### **Features**

Rugged construction for heavy duty application and prolonged lifetime - Two steel braid offers low volumetric expansion and optimum change in length characteristics - Abrasion resistant

#### Description

High pressure hose suitable for petroleum synthetic or water based hydraulic fluids in hydraulic systems - Suitable for general fluid power transmissions like earthmoving, forklifts trucks, heavy duty construction machinery, hoisting and handling equipment, high pressure equipment - Two steel braid design offers very high mechanical strength which prolongs lifetime of the hose in harsh conditions - Cover approved by MSHA (Mine Safety and Health Administration) - number IC-305.

## Temperature Range

-40 °C to 100 °C (-40 °F to 212 °F): limited to 70 °C (158 °F) for air and water based fluids

## Vacuum Rating

-0,93 bar; -700 mm Hg|-13,5 psi; -27,5 inch Hg

## Specifications

Meets the pressure performance rating of SAE 100R2.

### Standard Branding

TRANSFER OIL - TO HYDRAULIC - Part No - 2SB - TWO STEEL BRAIDS ANTIABRASION - Inch Size - DN Size - WP bar / psi - MSHA IC-305 - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

| Part no. | DN   | Inches | Dash | ID<br>(mm) | OD<br>(mm) | WP<br>(bar) | BP<br>(bar) | ID<br>(inch) | OD<br>(inch) | WP<br>(psi) | BP<br>(psi) | SF  | BR<br>(mm) | BR<br>(inch) | Weight<br>(gr/m) | Weight<br>(lb/ft) | Ferrule<br>standard | Ferrule<br>A316L |
|----------|------|--------|------|------------|------------|-------------|-------------|--------------|--------------|-------------|-------------|-----|------------|--------------|------------------|-------------------|---------------------|------------------|
| 0852     | DN6  | 1/4    | -4   | 6.4        | 12.8       | 400         | 1600        | 0.252        | 0.504        | 5800        | 23200       | 4:1 | 40         | 1.57         | 248              | 0.167             | SAC121              | SAC821           |
| 0853     | DN8  | 5/16   | -5   | 8.1        | 14.8       | 400         | 1600        | 0.319        | 0.583        | 5800        | 23200       | 4:1 | 50         | 1.97         | 312              | 0.210             | SAC131              | SAC831           |
| 0854     | DN10 | 3/8    | -6   | 9.8        | 16.8       | 330         | 1320        | 0.386        | 0.661        | 4700        | 18800       | 4:1 | 65         | 2.56         | 375              | 0.252             | SAC141              | SAC841           |
| 0855     | DN12 | 1/2    | -8   | 13.0       | 20.2       | 260         | 1040        | 0.512        | 0.795        | 3700        | 14800       | 4:1 | 85         | 3.35         | 474              | 0.319             | SAC151              | SAC851           |
| 0856     | DN16 | 5/8    | -10  | 16.3       | 23.7       | 220         | 880         | 0.642        | 0.933        | 3100        | 12400       | 4:1 | 115        | 4.53         | 561              | 0.377             | SAC161              | SAC861           |
| 0857     | DN20 | 3/4    | -12  | 19.5       | 27.8       | 150         | 600         | 0.768        | 1.094        | 2100        | 8400        | 4:1 | 170        | 6.69         | 717              | 0.482             | SAC171              | SAC871           |

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 24/11/2025

www.transferoil.com