



TRANSFER OIL

Pure Fluid Attitude



085 - 2SB - TWO STEEL BRAIDS ANTIABRASION

Thermoplastic hose with MSHA approved cover and double steel reinforcement, for high pressure hydraulic applications from 150 to 400 bar (2100 to 5800 psi)



FEATURES

Inner Tube

Polyester elastomer

Reinforcement

Two braids of steel wire

Cover

Polyurethane - black - non pinpricked - laser branding

Applications

General hydraulic applications requiring high mechanical protection properties of hose and braid combined with high pressure - Construction equipment - Hoisting and handling equipments - Machine tools

Features

Rugged construction for heavy duty application and prolonged lifetime - Two steel braid offers low volumetric expansion and optimum change in length characteristics - Abrasion resistant

Description

High pressure hose suitable for petroleum synthetic or water based hydraulic fluids in hydraulic systems - Suitable for general fluid power transmissions like earthmoving, forklifts trucks, heavy duty construction machinery, hoisting and handling equipment, high pressure equipment - Two steel braid design offers very high mechanical strength which prolongs lifetime of the hose in harsh conditions - Cover approved by MSHA (Mine Safety and Health Administration) - number IC-305.

Temperature Range

-40 °C to 100 °C (-40 °F to 212 °F): limited to 70 °C (158 °F) for air and water based fluids

Vacuum Rating

-0,93 bar; -700 mm Hg|-13,5 psi; -27,5 inch Hg

Specifications

Meets the pressure performance rating of SAE 100R2.

Standard Branding



TRANSFER OIL - TO HYDRAULIC - Part No - 2SB - TWO STEEL BRAIDS ANTIABRASION - Inch Size - DN Size - WP bar / psi - MSHA IC-305 - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
0852	DN6	1/4	-4	6.4	12.8	400	1600	0.252	0.504	5800	23200	4:1	40	1.57	248	0.167	SAC121	SAC821
0853	DN8	5/16	-5	8.1	14.8	400	1600	0.319	0.583	5800	23200	4:1	50	1.97	312	0.210	SAC131	SAC831
0854	DN10	3/8	-6	9.8	16.8	330	1320	0.386	0.661	4700	18800	4:1	65	2.56	375	0.252	SAC141	SAC841
0855	DN12	1/2	-8	13.0	20.2	260	1040	0.512	0.795	3700	14800	4:1	85	3.35	474	0.319	SAC151	SAC851
0856	DN16	5/8	-10	16.3	23.7	220	880	0.642	0.933	3100	12400	4:1	115	4.53	561	0.377	SAC161	SAC861
0857	DN20	3/4	-12	19.5	27.8	150	600	0.768	1.094	2100	8400	4:1	170	6.69	717	0.482	SAC171	SAC871

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.
 Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.
 Document date: 05/08/2025
www.transferoil.com